

Leica HDS6000

A new generation of ultra-high speed laser scanner

See also
HDS6000
brochure!



Compact design and high-performance scanning optimize field productivity

Leica HDS6000: new standard for phase-based scanners

The “next-generation” Leica HDS6000 significantly reduces field costs and increases phase-based data quality for many types of as-built and site surveys where users want to take advantage of ultra-high speed, phase-based laser scanning.

Up to 500,000 points per second

The Leica HDS6000 features the fastest scan rates available for high-accuracy, as-built surveys, making it the ideal instrument when very short time windows are available for capturing High-Definition Survey™ data.

Highly portable and field-efficient

By integrating the scanner, data storage, scanner control, and batteries into a single unit, the Leica HDS6000 is easy to setup and carry for fast project execution.

In addition, its increased range (up to 79m for 90% surface reflectivity), improved accuracy, and dual-axis (tilt) sensing capability can reduce the number of instrument and target setups needed, further cutting field time. These same features also increase the versatility of phase-based scanning.

Flexible scan control & registration options

Users can choose from three scanner control options. A side touch panel allows simple control. An optional wireless PDA allows “touch-free” control, plus visual inspection of jpeg scan images. For full 3D viewing, scan measurement, and rigorous quality assurance (QA), users can opt for powerful laptop control with Leica Cyclone SCAN, the industry’s most popular and versatile scanner control software. For accurately registering (or stitching) multiple scans together, Leica Cyclone REGISTER software lets Leica HDS6000 users take advantage of either scan targets or “cloud-to-cloud” registration methods that don’t require targets.

- when it has to be **right**

Leica
Geosystems

Leica HDS6000

Product Specifications

General	
Instrument type	Compact, phase-based, dual-axis sensing, ultra high-speed laser scanner, with survey-grade accuracy and full field-of-view
User interface	Onboard touch panel, or external notebook or Tablet PC, or PDA
Scanner drive	Servo motor
Data storage	Integrated hard drive
Camera	No integrated camera; Cyclone SCAN supports use of external camera

System Performance	
Accuracy of single measurement	
Position*	6mm, 1m to 25m range; 10mm to 50m range
Distance*	≤4mm at 90% albedo up to 25m; ≤5mm at 18% albedo up to 25m; ≤5mm at 90% albedo up to 50m; ≤6mm at 18% albedo up to 50m
Angle (horizontal/vertical)	125 µrad/125 µrad, one sigma
Modeled surface precision**/noise	2mm at 25m; 4mm at 50m for 90% albedo, one sigma; 3mm at 25m; 7mm at 50m, for 18% albedo, one sigma

Target acquisition***	2mm std. deviation
Dual-axis sensor	Selectable on/off; 3.6" resolution
Data integrity monitoring	Self-check at start-up; optional checks using Cyclone-SCAN

Laser Scanning System	
Type	Phase-shift
Laser Class	3R (IEC 60825-1)
Range	79m ambiguity interval 79m @90%; 50m @18% albedo
Scan rate	Up to 500,000 points/sec, maximum instantaneous rate; Average time: see "Selectability Table" below

Scan resolution																						
Spot size	3mm at exit (based on Gaussian definition) + 0.22mrad divergence; 8mm @25m; 14mm @50m																					
Selectability	5 pre-set spacings per table																					
	<table border="1"> <tr> <th></th> <th>Pts/360°</th> <th>Scan time</th> </tr> <tr> <td></td> <td>(vert., horiz.)</td> <td>(full dome)</td> </tr> <tr> <td>"Preview"</td> <td>1250</td> <td>25 sec</td> </tr> <tr> <td>Middle (4x)</td> <td>5000</td> <td>1 min 40 sec</td> </tr> <tr> <td>High (8x)</td> <td>10000</td> <td>3 min 22 sec</td> </tr> <tr> <td>Super High (16x)</td> <td>20000</td> <td>6 min 44 sec</td> </tr> <tr> <td>Ultra High (32x)</td> <td>40000</td> <td>26 min 40 sec</td> </tr> </table>		Pts/360°	Scan time		(vert., horiz.)	(full dome)	"Preview"	1250	25 sec	Middle (4x)	5000	1 min 40 sec	High (8x)	10000	3 min 22 sec	Super High (16x)	20000	6 min 44 sec	Ultra High (32x)	40000	26 min 40 sec
	Pts/360°	Scan time																				
	(vert., horiz.)	(full dome)																				
"Preview"	1250	25 sec																				
Middle (4x)	5000	1 min 40 sec																				
High (8x)	10000	3 min 22 sec																				
Super High (16x)	20000	6 min 44 sec																				
Ultra High (32x)	40000	26 min 40 sec																				
Point spacing at range	@10m @50m																					
	<table border="1"> <tr> <th></th> <th>@10m</th> <th>@50m</th> </tr> <tr> <td>"Preview"</td> <td>50.6x50.6mm</td> <td>250x250mm</td> </tr> <tr> <td>Middle (4x)</td> <td>12.6x12.6mm</td> <td>62x62mm</td> </tr> <tr> <td>High (8x)</td> <td>6.3x6.3mm</td> <td>31.4x31.4mm</td> </tr> <tr> <td>Super High (16x)</td> <td>3.1x3.1mm</td> <td>15.8x15.8mm</td> </tr> <tr> <td>Ultra High (32x)</td> <td>1.6x1.6mm</td> <td>7.9x7.9mm</td> </tr> </table>		@10m	@50m	"Preview"	50.6x50.6mm	250x250mm	Middle (4x)	12.6x12.6mm	62x62mm	High (8x)	6.3x6.3mm	31.4x31.4mm	Super High (16x)	3.1x3.1mm	15.8x15.8mm	Ultra High (32x)	1.6x1.6mm	7.9x7.9mm			
	@10m	@50m																				
"Preview"	50.6x50.6mm	250x250mm																				
Middle (4x)	12.6x12.6mm	62x62mm																				
High (8x)	6.3x6.3mm	31.4x31.4mm																				
Super High (16x)	3.1x3.1mm	15.8x15.8mm																				
Ultra High (32x)	1.6x1.6mm	7.9x7.9mm																				

Field-of-view (per scan)	
Horizontal	360° (maximum)
Vertical	310° (maximum)
Aiming/Sighting	Optical horizontal sighting using QuickScan™ feature

Scanning Optics	Vertically rotating mirror on horizontally rotating base; Environmentally protected by shield
Scan motors	Direct drive, brushless; proprietary
Power transfer	Onboard rotating turret or external to non-rotating base
Data transfer	Ethernet or USB 2.0 device (two ports)

Data storage capacity (onboard)	60 GB, min
Communications	DHCP client/server; Ethernet or Bluetooth
Status indicators	4-line alphanumeric display for laser status, system power & status 1 LED for laser status
Level indicator	External bubble; digital readout on touch panel or via laptop

Electrical	
Power supply	24V DC; 90 - 260V AC
Power Consumption	50 W
Battery Type	Integrated: Li-ion External: sealed lead acid
Duration	Internal: 1.5 hrs, typical External: 4 hrs, typical

Power status indicators	LEDs indicate charging status and capacity levels
--------------------------------	---

Environmental	
Operating temp.	0° C to +40° C
Storage temp.	-20°C to +50°C
Lighting	Fully operational between bright sunlight and complete darkness
Humidity	Non-condensing

Physical	
Scanner	
Dimensions	7.5"D x 9.6" W x 13.8" H 190mm D x 244mm W x 351.5mm
Weight	14 kg, nominal (includes integrated battery)

Battery (external)	
Dimensions	9.5" D x 10" W x 12" H 240mm D x 260 mm W x 300mm H
Weight	16 kg, nominal

AC Power Supply	
Dimensions	9.5" D x 5" W x 6" H 240mm D x 127 mm W x 152mm H
Weight	2.5 kg, nominal

Standard Accessories	
Scanner and accessory carrying case Additional rechargeable integrated battery Charging/power cable, ethernet cable, A/C cable Battery charger / A/C power supply Battery charging cradle for internal battery Cyclone™-SCAN software Cleaning kit	

Hardware Options	
Notebook PC, Tablet PC, or PDA HDS6000 scan targets and target accessories Service agreement for Leica HDS6000 Extended warranty for Leica HDS6000 Tribrach (Leica Professional Series) Survey tripod (Leica Professional Series) External battery	

Notebook PC for scanning Δ	
Component	required (minimum)
Processor	1.7 GHz Pentium M or similar
RAM	1024MB SDRAM
Network card	Ethernet
Display	SXGA+ (64 MB or greater video RAM rec.)
Operating system	Windows XP Professional (SP1 Or higher) Windows 2000 (SP3 or higher with up to date security patches)

PDA for scanning (rec.)	
HP iPAQ Pocket PC Series Windows Mobile 5.0 for Pocket PC; iPAQ Wireless application; Bluetooth wireless technology	

Cyclone-SCAN	
Scan density control from five (5) pre-sets Scan filters: range, intensity ¹ Scan speed control (default or low) Laser power control (normal or low/close-in) Selection of scan area via scribed rectangle or pre-sets ¹ Customizable longitude/latitude grid lines Pre-scan range probe	

Script management for auto scan sequencing ¹ View scanner locations and field-of-view Level of detail (LOD) for fast visualization Auto rechecking (re-acquisition) of targets ¹ Target identification Traverse ² ; traverse & resection reports Field Setup - Resection; Known Backsight; Known Azimuth ¹ Direct coordinate/station entry ¹ Dual-axis sensor on/off Stakeout and ID point Target and instrument height input Support of external digital images	
--	--

Fly-around, pan & zoom, rotate clouds, meshes, models in 3D View point clouds with intensity or true-color mapping Point-and-scan QuickScan to set horizontal FoV ¹ User-defined quality-of-fit checks Measure & dimension: slope dist., ΔX, ΔY, ΔZ Create, manage annotations and layers Save/restore views; save screen images; undo/redo support	
--	--

Onboard touch panel control	
Vertical, horizontal FOV Scan density: 5 levels Dual-axis sensor on/off Laser power setting for normal or close-in mode	

PDA control	
Vertical, horizontal FOV Scan density: 5 levels Dual-axis sensor on/off Laser power setting for normal or close-in mode Display jpeg thumbnail of scan image	

Direct Import Formats	
Cyclone native IMP object database format, Cyclone Object ASCII point data (XYZ, SVY, PTS, PTX, TXT); Leica's X-Function DBX format, LandXML, ZFS, ZFC, 3DD	

Direct Export Formats	
ASCII point data (XYZ, SVY, PTS, PTX, TXT); Leica's X-Function DBX format, LandXML, PTZ	

Indirect Export Formats	
AutoCAD (via COE for AutoCAD plug-in) MicroStation (via COE for MicroStation plug-in) PDS (via MicroStation, COE for MicroStation plug-in) AutoPLANT (via AutoCAD, COE for MicroStation plug-in)	

Ordering Information	
Contact Leica Geosystems or authorized representatives	

All specifications are subject to change without notice.
All +/- accuracy specifications are one sigma unless otherwise noted.
¹ SmartScan™ technology feature
Δ Minimum requirements for modeling operations are different. Refer to Cyclone data sheet specifications.
* At 1m - 50m range, one sigma
** One sigma; subject to modeling methodology for modeled surface
*** Algorithmic fit to planar HDS gray & white targets

Laser class 3R in accordance with IEC 60825-1 resp. EN 60825-1

The **Bluetooth**® word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Leica Geosystems AG is under license. Windows is a registered trademark of Microsoft Corporation. Other trademarks and trade names are those of their respective owners.

Illustrations, descriptions and technical specifications are not binding and may change. Printed in Switzerland - Copyright Leica Geosystems AG, Heerbrugg, Switzerland 2007.
758948en - XI.07 - RDV